



**NOTE:** To accommodate customer preferences, the Control Console and SANI-DESIGN<sup>™</sup> Cleaning Cap Assembly is **not** factory installed on the bath deck. An installation kit for the SANI-DESIGN<sup>™</sup> Cleaning Cap, and a 6 ft. cable with installation instructions for connecting the Control Console to the control box are provided with all baths.

Patents recieved or pending.

Note: Dimensional Tolerances: ±1/4"

	RE527	RE553	RE630
<b>Drop-in-Hole Size:</b>	30" x 58"	34" x 64"	34" x 70"
<b>Operating Capacity:</b>	39 gal	48 gal	53 gal
<b>Overflow Capacity:</b>	62 gal	75 gal	83 gal
<b>Floor Loading / sq.ft.:</b>	54.5 lbs	51.1 lbs	50.3 lbs
<b>Cartoned Wt: AirMasseur</b>	106 lbs	125 lbs	133 lbs
<b>Cartoned Wt: Soaker</b>	68 lbs	87 lbs	95 lbs
<b>Cube:</b>	28.1 cu.ft.	36.6 cu.ft.	39.8 cu.ft.
<b>Construction:</b>	Fiberglass reinforced acrylic bath with Level Form <sup>™</sup> full-support base		

We provide products listed with Underwriters Laboratories, Inc. (UL), International Association of Plumbing and Mechanical Officials (IAPMO), and Canadian Underwriters Laboratory (CUL). Consult factory with your listing requirements.

<b>Standard</b>	 <p>1 hp, variable speed blower with integral air heater and electronic control with 20 minute timer and automatic purge cycle. Contoller operates blower, blower speed for continuous or massage mode. Requires one (1) 120V 20A dedicated GFCI-protected circuit.</p>
<b>Signature</b>	 <p>1 hp, variable speed blower with integral air heater and digital control with 20-minute timer and automatic purge cycle. Controllor operates blower, blower speed for for continuous, wave or pulse massage mode. Shows blower speed and time remaining. Includes LED mood light and floating universal remote control that operates all bath functions plus TV, DVD, CD, etc. Requires two (2) 120V 20A dedicated GFCI-protected circuits.</p>